

(19)

Europäisches Patentamt

European Patent Office

Office européen des brevets

RECEIVED

18 AUG 2003



(11)

EP 0 858 780 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

19.08.1998 Bulletin 1998/34

(51) Int. Cl.⁶: A61B 17/60

(21) Application number: 97122920.8

(22) Date of filing: 28.12.1997

(84) Designated Contracting States:

AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC
NL PT SE

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: 13.02.1997 IT VR970011

(71) Applicant: ORTHOFIX S.r.l.

37012 Bussolengo (VR) (IT)

(72) Inventors:

- Faccloli, Giovanni
46040, Monzambano - Mantova (IT)
- Venturini, Daniele
37065 Povegliano Veronese - Verona (IT)
- Ten Veldhuys, Sander
37138 Verona (IT)

(74) Representative:

O'Byrne, Daniel Joseph
c/o Fenzi & Associati,
25, Via Savai
37124 Verona (IT)

(54) Orthopaedic apparatus, particularly for the surgical correction of bone deformations

(57) An orthopaedic apparatus, particularly for the surgical correction of angular and longitudinal defects of the bones of limbs, of the femur and tibia type, comprising a longitudinal rod (2) externally positionable substantially parallel to a bone for correction, a first clamp (3) movably anchored to the rod (2) for supporting drilling guides for screws insertable in a proximal portion of the bone, and at least one second clamp (4) movably anchored to the rod for supporting drilling guides for screws insertable in a distal portion of the bone. The first and second clamps are orientatable and selectively blockable, before the surgical intervention, in predetermined angular positions with respect to the rod (2) corresponding to the angular deformations of the bone, and are repositionable with respect to the rod in correct angular positions after the osteosynthesis of the proximal and distal portions of the bone so as to eliminate the angular deformations of the bone.




Fig. 1

Description

Technical Field

The present invention relates to an orthopaedic apparatus, particularly for the surgical correction of bone deformations, for example of the tibia and of the femur.

Background Art

It is known that adjustable external fixation devices are commonly utilised for correcting certain angular and longitudinal deformations of long bones. Such devices essentially comprise groups of bone screws fixed in the bone portions affected by angular defects and held by clamps which are in turn slidably mounted on longitudinal guides externally positionable at the limb to be reconstructed.

The correction normally is carried out gradually with the aid of compressor-distractor devices which act on the mobile clamps while the bone callous regenerates itself allowing a certain degree of deformation.

This methodology, however much effective, requires correction times which are rather long and does not give any immediate result for the patient.

Disclosure of the Invention

The present invention in accordance with one preferred aspect proposes to carry out an integral and immediate correction in the operating room of the defects obtained preliminarily by the surgeon by means of normal radiological procedures.

With this principal aim in mind, there is provided an orthopaedic apparatus, particularly for the surgical correction of angular and longitudinal defects of the bones of limbs, of the femur and tibia type, which comprises a longitudinal rod externally positionable substantially parallel to a bone for correction, a first clamp movably anchored to said rod for supporting drilling guides for screws insertable in a proximal portion of the bone, and at least one second clamp movably anchored to said rod for supporting drilling guides for screws insertable in a distal portion of the bone, said first and second clamps being orientatable and selectively blockable, before the surgical intervention, in predetermined angular positions with respect to said longitudinal rod corresponding to the angular deformations of the bone, and being repositionable with respect to said rod in correct angular positions after the osteosynthesis of the proximal and distal portions of the bone so as to eliminate the angular deformations of the bone.

Brief Description of Drawings

The characteristics and advantages of the invention will become apparent from the description of some pre-

ferred but not exclusive embodiments of the apparatus according to the invention, illustrated for illustrative and non-limiting purposes with the help of the attached drawing sheets in which:

Fig. 1 illustrates a general front elevation view of the orthopaedic apparatus according to one preferred aspect of the invention applied to a bone to be corrected;

Fig. 2 illustrates an enlarged scale detail of the apparatus of Fig. 1;

Fig. 3 illustrates a top plan view of the detail of Fig. 2;

Fig. 4 illustrates a sectional view of Fig. 1 taken according to the plane III-III and shows another enlarged scale detail of the apparatus of Fig. 1;

Fig. 5 illustrates a bottom view of the detail of Fig. 4.

Best Modes for Carrying Out the Invention

With reference to the cited figures, an orthopaedic apparatus for use in an operating room according to one preferred aspect of the invention, indicated globally by the reference numeral 1, comprises essentially a longitudinal rod 2 upon which a first end clamp 3 and a second end clamp 4, for supporting drill guides for bone screws (not shown in the drawings), are movably mounted.

The rod 2 defines a longitudinal axis Y, and has a semicircular transverse cross-section and a flat face 5 with a central longitudinal groove 6 and an elongated hole 7 which extend for nearly the entire length of the rod.

Preferably, the longitudinal groove 6 has a trapezoidal shape with the smaller side towards the flat face 5.

The first clamp 3 is substantially T-shaped with a portion 8 for connection to the rod 2 provided on its opposed faces with dovetail tenons 9, 10 counter-shaped with respect to the longitudinal groove 6. The clamp 3 is anchored to the rod by means of one of its tenons 9, 10 inserted in the groove 6, in proximity to one of its longitudinal ends, and is blocked thereat by means of a screw with a knob 11.

A supporting portion 12, for drilling guides of the bone screws insertable in the proximal portion of the bone, is united to the connecting portion 8, and is in turn formed by a substantially flat base plate 13 with two recesses 14 upon which a cover 16 also provided with recesses 17 is hinged at 15. The cover 16 is blocked against the base by means of a screw with a knob 18 so as to lock the drilling guides for the screws, with variable inclinations, between the recesses 14, 17.

The portion 12 is united to the portion 8 of the clamp 3 by means of an intermediate element 19 which has a first hinge axis A and a second hinge axis B, substantially perpendicular with respect to one another and with respect to the axis Y when the clamp 3 is anchored to the rod 2. In order to selectively block the angular

position of the intermediate element 19 with respect to the connecting portion 8 about the axis B there is provided a first eccentric stop 20 with a hexagonal set head. In order to selectively block the angular position of the intermediate element 19 with respect to the supporting portion 12 about the axis A there is provided a second eccentric stop 20' also having a hexagonal set head.

In order to maintain the two axes A, B in preferential position there are provided sphere positioning means 21 elastically compressed by a spring against a countershaped seat formed on each axis.

There are provided distancing means constituted by a screw 22 which is screwed in a threaded hole formed in the central part of the plate 13 and having a hexagonal set head 23 and an abutment end 24 supportable at the bone. Other distancing means, for rigidly holding the bone portion in position during drilling, are constituted by Kirschner wires, not shown in the drawings, fixed in the bone and passing through calibrated holes 25 provided in the base plate 13 and calibrated holes 26 provided in the cover 16.

The second clamp 4 is essentially constituted by a second supporting portion 27, in turn formed by a base 28 upon which a cover 30 is hinged at 29. The base and the cover have facing seats 31 for holding drilling guides for the screws insertable in the distal portion of the bone, not shown in the drawings, by means of a locking action provided by a screw with a knob 32.

The base 28 has a protruding appendix 33 with an end pin 34 inserted in an arcuate groove 35 with centre C formed in a transversal circular arc element 36 having on one of its flat faces a graduated scale 37 for measuring the torsion angle of the clamp.

The centre C of the groove 35 should coincide approximately with the axis of the bone when the clamp 4 is mounted on the rod 2 and defines a third correction axis, perpendicular to the first two A, B, of the distal portion of the bone affected by torsion.

For blocking the angular position of the clamp 4, there is provided a screw with knob 38 which is screwed on the appendix 33.

There are provided distancing means constituted by a screw 39 which is screwed in a threaded hole formed in the appendix 28 and having ends adapted to be supported at the distal portion of the bone to be corrected.

At the extremities of the flat element 36 there are formed connection tenons 40, 40' which permit a right or left mounting on the rod 2 according to the requirements. The tenons 40, 40' may be inserted in the groove 6 of the rod 2 and be blocked in position by means of a screw with knob 41 which is screwed in respective threaded holes 42, 43 formed in correspondence with tenons 40, 40'.

In operation, the surgeon obtains with x-rays on multiple planes the angles of the angular defects of the proximal portion and of the torsion defects of the distal

portion, and then imposes and blocks such angles on the clamps 3, 4 and mounts the latter on the rod 2. Thereafter the drilling of the bone in correspondence with the proximal and distal portions is carried out by using the drilling guides blocked on the clamps 3, 4. Then the osteotomy of the bone in correspondence with the proximal and distal portions is carried out and the clamps are brought back in correct position towards the rest position imposed by the preferential positioning means eliminating the angular defects of the bone. Finally, the clamps of the apparatus are substituted with those of an external fixator which sustains the limb for the entire period of growth of the bone callous up to complete recovery.

Claims

1. Orthopaedic apparatus, particularly for the surgical correction of angular and longitudinal defects of the bones of limbs, of the femur and tibia type, comprising a longitudinal rod (2) externally positionable substantially parallel to a bone for correction, a first clamp (3) movably anchored to said rod for supporting drilling guides for screws insertable in a proximal portion of the bone, and at least one second clamp (4) movably anchored to said rod for supporting drilling guides for screws insertable in a distal portion of the bone, said first and second clamps being orientatable and selectively blockable, before the surgical intervention, in predetermined angular positions with respect to said longitudinal rod corresponding to the angular deformations of the bone, and being repositionable with respect to said rod in correct angular positions after the osteosynthesis of the proximal and distal portions of the bone so as to eliminate the angular deformations of the bone.
2. Orthopaedic apparatus according to claim 1, wherein said first clamp has a supporting portion (12) for said drilling guides united to a first portion (8) for connection to said rod by means of first (A) and second (B) mutually perpendicular hinging axes.
3. Orthopaedic apparatus according to claim 1, wherein said connection portion of said first clamp is anchorable to said rod such that said first and second hinging axes are perpendicular to the longitudinal axis (Y) of the rod.
4. Orthopaedic apparatus according to claim 1, wherein said first clamp (3) has preferential positioning means for maintaining said supporting portion in operative position substantially orthogonal with respect to said rod.
5. Orthopaedic apparatus according to claim 2, wherein said preferential positioning means are of

the sphere (21) type elastically compressed in a centering seat formed on each hinging axis.

6. Orthopaedic apparatus according to claim 5, wherein said supporting portion (12) comprises a base plate (13), a cover (16) hinged on said base (13) and a blocking knob (18) for blocking said cover against said base locking therebetween the drilling guides. 5
7. Orthopaedic apparatus according to claim 6, wherein said first clamp (3) has adjustable distancing means for positioning said supporting portion with respect to the facing bone portion. 10
8. Orthopaedic apparatus according to claim 7, wherein said distancing means comprise a screw (22) screwed in a threaded hole provided in a substantially central position of said base plate. 15
9. Orthopaedic apparatus according to claim 7, wherein said distancing means comprise one or more Kirschner wires insertable in the proximal portion of the bone in calibrated holes (25, 26) formed in said base plate and in said cover. 20 25
10. Orthopaedic apparatus according to claim 1, wherein said second clamp (4) comprises a second supporting portion (27) for the drilling guides connected to a second portion (36) for connecting to said rod by means of circular arcuate guide means (35) with an axis (C) substantially coincident with the axis of the bone to be corrected. 30
11. Orthopaedic apparatus according to claim 10, wherein said circular arcuate guide means (35) extend in a transversal plane when said second connecting portion is anchored to said rod. 35
12. Orthopaedic apparatus according to claim 1, wherein said second supporting portion (27) comprises a base (28) and a cover (30) as well as screw distancing means (39) for maintaining said second claim (4) at a predetermined distance with respect to the distal portion of the bone to be corrected. 40 45
13. Orthopaedic apparatus according to claim 12, wherein said rod (2) has a longitudinal seat (6) with a substantially trapezoidal transverse cross section for slidably holding first (8) and second (40, 40') connecting portions with dovetail shape of said clamps. 50









Fig. 1







Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 0 858 780 A3

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:
06.05.1999 Bulletin 1999/18

(51) Int. Cl.⁶: A61B 17/60

(43) Date of publication A2:
19.08.1998 Bulletin 1998/34

(21) Application number: 97122920.8

(22) Date of filing: 28.12.1997

(84) Designated Contracting States:
AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC
NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• Faccioli, Giovanni
46040, Monzambano - Mantova (IT)
• Venturini, Daniele
37065 Povegliano Veronese - Verona (IT)
• Ten Veldhuys, Sander
37138 Verona (IT)

(30) Priority: 13.02.1997 IT VR970011

(71) Applicant: ORTHOFIX S.r.l.
37012 Bussolengo (VR) (IT)

(74) Representative:
O'Byrne, Daniel Joseph
c/o Fenzl & Associati,
25, Via Savai
37124 Verona (IT)

(54) **Orthopaedic apparatus, particularly for the surgical correction of bone deformations**

(57) An orthopaedic apparatus, particularly for the surgical correction of angular and longitudinal defects of the bones of limbs, of the femur and tibia type, comprising a longitudinal rod (2) externally positionable substantially parallel to a bone for correction, a first clamp (3) movably anchored to the rod (2) for supporting drilling guides for screws insertable in a proximal portion of the bone, and at least one second clamp (4) movably anchored to the rod for supporting drilling guides for screws insertable in a distal portion of the bone. The first and second clamps are orientatable and selectively blockable, before the surgical intervention, in predetermined angular positions with respect to the rod (2) corresponding to the angular deformations of the bone, and are repositionable with respect to the rod in correct angular positions after the osteosynthesis of the proximal and distal portions of the bone so as to eliminate the angular deformations of the bone.




Fig. 1



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 97 12 2920

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
Y	US 5 152 280 A (DANIELI GUIDO) 6 October 1992 * claim 1; figure 6 *	1-4	A61B17/60 A61B17/17 A61B17/58
Y	WO 96 35386 A (ELECTRO BIOLOGY INC ;MAHAFFEY JOHN SCOTT (US); BAILEY KIRK JAY (US) 14 November 1996 * page 19, line 24 - page 20, line 8; figures 20,21 *	1-4	
A	WO 96 05777 A (ORTHOFIX SRL ;RENZI BRIVIO LUDOVICO (IT); LAVINI FRANCO (IT); FACC) 29 February 1996 * page 9, paragraph 3 *	1	
A	US 4 920 959 A (WITZEL ULRICH ET AL) 1 May 1990 * abstract; figure 1 *	1	
A	US 4 628 922 A (DEWAR MICHAEL E) 16 December 1986 * abstract; figure 1 *	1	TECHNICAL FIELDS SEARCHED (Int.Cl.6)
A	DE 42 38 582 A (BRUG ERWIN PROF DR MED) 19 May 1994 * abstract; figure 1 *	1	A61B
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 17 March 1999	Examiner Hansen, S
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 97 12 2920

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

17-03-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5152280 A	06-10-1992	AT 152596 T	15-05-1997
		DE 68928032 D	12-06-1997
		DE 68928032 T	21-08-1997
		WO 9007305 A	12-07-1990
		EP 0404897 A	02-01-1991
		ES 2100879 T	01-07-1997
		JP 2725884 B	11-03-1998
		JP 3504453 T	03-10-1991
WO 9635386 A	14-11-1996	US 5662650 A	02-09-1997
		AU 5856896 A	29-11-1996
WO 9605777 A	29-02-1996	IT VR940075 A	23-02-1996
		AU 696067 B	03-09-1998
		AU 3347195 A	14-03-1996
		BR 9506329 A	05-08-1997
		CA 2156678 A	24-02-1996
		CN 1125557 A	03-07-1996
		EP 0724410 A	07-08-1996
		JP 9504462 T	06-05-1997
		US 5728096 A	17-03-1998
		ZA 9507007 A	09-04-1996
US 4920959 A	01-05-1990	DE 3611319 A	15-10-1987
		AT 71502 T	15-02-1992
		CA 1318820 A	08-06-1993
		DE 3775958 T	27-02-1992
		WO 9312729 A	08-07-1993
		EP 0240034 A	07-10-1987
		GR 3003590 T	16-03-1993
US 4628922 A	16-12-1986	EP 0177270 A	09-04-1986
		GB 2164859 A,B	03-04-1986
DE 4238582 A	19-05-1994	NONE	